



## Din 934

## Hexagon nut (thickness 0,8 d)

Steel cl.6 -cl.8- cl.10  
Stainless steel  
Brass (1)  
Polyamide

Designation: hexagon nut, thickness 0,8 d, Ø 12mm, normal metric draad = DIN 934M 12

d	s	e	m	weights in (kg) per 1000 pieces.	Packaging
M2	4	4.38	1.6	0.14	500
M 2.5	5	5.51	2	0.28	
M3	5.5	6.08	2.4	0.38	
M4	7	7.74	3.2	0.81	200
M5	8	8.87	4	1.23	
M6	10	11.05	5	2.5	
M7	11	12.12	5.5	3.12	
M8	13	14.38	6.5	5.2	100
M10	17	18.9	8	11.6	
M12	19	21.1	10	17.3	
M14	22	24.49	11	25	
M16	24	26.75	13	33.3	
M18	27	30.14	15	49.4	50
M20	30	33.53	16	64.4	
M22	32	35.72	18	79	
M24	36	39.98	19	110	
M27	41	45.63	22	165	25
M30	46	51.28	24	223	
M33	50	55.8	26	288	
M36	55	61.31	29	393	
M39	60	66.96	31	502	
M42	65	72.61	34	652	
M45	70	78.26	36	800	
M48	75	83.91	38	977	
M52	80	89.56	42	1220	
M56	85	95.07	45	1420	
M60	90	99.21	48	1690	
M64	95	104.86	51	1980	
M68	100	110.51	54	2300	
M72x6	105	116.16	58	2670	
M76x6	110	121.81	61	3040	
M80x6	115	127.46	64	3440	
M85x6	120	133.11	68	3930	
M90x6	130	144.08	72	4930	
M100x6	145	161.02	80	6820	
M110x6	155	172.32	88	8200	
M125x6	180	200.57	100	13000	
M140x6	200	220.8	112	17500	
M160x6	230	254.7	128	26500	

(1) in case of brass, weights are to be multiplied by 1.08.

Execution : A (formerly m) ≤ M16 as per DIN ISO 4759/1

B (formerly mg) > M16 as per DIN ISO 4759/1